

Market leader for petrol station- and chemical tanks

Safe products – quick to install and reliable for decades.
50 years experience in leak protection linings.

Approved media for our well-established products:

	DIBt-Approval Z-65.30-562	FENOSAFE® FUEL	FENOSAFE® CHEMICAL	FENOSAFE® YELLOW	FENOSAFE® BLACK
	Media				
1	Petrol fuels (gasoline) in accordance with DIN EN 228 with a maximum ethanol content of 20 %	☺	☺	☺	
2	Diesel fuel in accordance with DIN EN 590, or mixtures of Diesel fuel and a maximum of 20 % fatty acid methyl ester (FAME) in total	☺	☺	☺	
3	Heating oil EL – unused combustion engine oils, unused Motor vehicle transmission oils	☺			
4	Used combustion engine oils and used motor vehicle transmission oils	☺			
6	Aviation fuel 100 LL	☺	☺		
6	Jet-A1 aviation turbine fuel with additives (NATO code F-34)	☺			
7	All alcohols and glycol ethers	☺			
8	All organic esters and ketones (biodiesel)	☺	☺		
9	Organic acids (carboxylic acids, except formic acid) and their salts		☺		
10	Aqueous solutions of organic tensides		☺		
11	Crude oil	☺			
12	All hydrocarbons, including benzene and mixtures containing benzene Mono- and polycyclic aromatic hydrocarbons	☺			
13	Aqueous solutions of organic acids up to 10 %		☺		
14	Mineral acids up to 20 %				☺
15	Non-organic lyes				☺
16	Aqueous solutions of inorganic non-oxidising salts				☺
17	Paraffinic diesel fuel with a FAME content of < 7 % (HVO, GTL etc.)			☺	

